

Dräger VarioGard® 3000 Toxic Gas Detection

The Dräger VarioGard® 3000 EC is a digital transmitter with an integrated electrochemical sensor. It detects oxygen and toxic gases in the ambient air. This affordable system component makes it easier for you to configure a gas warning system.



Benefits

Digital function

The Dräger VarioGard 3000 EC is connected with the controller via the digital VarioGard bus. This is how it is supplied with electricity and how it transmits its measuring results. You can easily control the entire VarioGard system via the VarioGard bus.

High reliability

The VarioGard 3000 EC is equipped with an electrochemical DrägerSensor. This sensor measures the concentration of toxic gases in the ambient air. The measured values are transmitted digitally to the controller and displayed there. An alarm is triggered if the gas concentration exceeds one or more of the limit values configured.

Easy operation

The operation is extremely easy. You can make all configurations comfortably from the controller using VarioGard software. You can configure and monitor four current limit values and four averages over time for each transmitter. The alarms are optically and acoustically displayed on the transmitter and transmitted to the controller. A three-colour LED indicates the operating status of the transmitter. The calibration is controlled using a magnetic wand via contact points.

Individually configurable

The VarioGard 3000 EC is adaptable to your needs. This means that you have different sensors available depending upon the desired use:

CO, NO₂ and NO for garages, O₂ for oxygen supplies and NH₃ for cooling facilities, for example.

In addition, you can place the cable inlets on all four sides of the transmitter. The transmitter can be mounted vertically as well as horizontally.

Technical Data

Type	Transmitter for the measurement of concentrations of gases in the ambient air
Gases and measuring ranges	Carbon monoxide CO 0 to 300 ppm Ammonia NH ₃ 0 to 1200 ppm Oxygen O ₂ 0 to 25 vol. % Nitrogen monoxide NO 0 to 50 ppm Nitrogen dioxide NO ₂ 0 to 20 ppm
Display	3-colour LED (green, yellow, red): operation, maintenance, alarm
Input	2 function buttons
Alarm output	Horn and red LED
Alarms	8 configurable alarm limits
Electrical data	3-wire cable 16 to 30V DC, GND, Dräger VarioGard bus
Ambient conditions	Temperature -20 to 50 °C Humidity 10 to 95 % r. h., non-condensing Pressure 700 to 1300 hPa
Regulations/standards	VDI 2053 (2004) Air treatment systems for car parks EN 50545-1 Electrical apparatus for the detection and measurement of toxic and combustible gases in car parks and tunnels
Dimensions (with a cable inlet)	120 x 110 x 60 mm (WxHxD) plastic 120 x 120 x 60 mm (WxHxD) aluminium
Weight	0.4 kg plastic 1.0 kg aluminium
Housing	Plastic ABS light grey RAL 7035 IP 65 Aluminium light grey RAL 7035 IP 65
Cable inlet	M20 x 1.5, 6 – 12 mm

Ordering Information

VarioGard 3000 EC CO PL (plastic housing)	83 22 050
VarioGard 3000 EC NO ₂ PL (plastic housing)	83 22 051
VarioGard 3000 EC NH ₃ PL (plastic housing)	83 22 052
VarioGard 3000 EC O ₂ PL (plastic housing)	83 22 053
VarioGard 3000 EC NO PL (plastic housing)	83 22 054
VarioGard 3000 EC CO AL (aluminium housing)	83 22 055
VarioGard 3000 EC NO ₂ AL (aluminium housing)	83 22 056
VarioGard 3000 EC NH ₃ AL (aluminium housing)	83 22 057
VarioGard 3000 EC O ₂ AL (aluminium housing)	83 22 058
VarioGard 3000 EC NO AL (aluminium housing)	83 22 059
Calibration adapter VarioGard 3x00	83 22 015
Magnetic wand	45 43 428
VarioGard system technical handbook	90 33 191
Software set VarioGard 3x00 (including USB adapter)	83 22 016
Cable inlet M20 x 1.5 (set of 10)	83 15 420
VarioGard Instructions for Use	90 33 185

Notes

CORPORATE HEADQUARTERS
 Drägerwerk AG & Co. KGaA
 Moislinger Allee 53–55
 23558 Lübeck, Germany
www.draeger.com

Manufacturer:
 Dräger Safety AG & Co. KGaA
 Revalstraße 1
 23560 Lübeck, Germany

Revendedor:



NR Pro Engenharia e Com. Ltda.
 Rua Prof. Pedreira de Freitas,
 1473 - São Paulo - SP
 (11) 2293-5221

SYSTEM CENTERS
P. R. CHINA
 Draeger Safety Equipment
 (China) Co., Ltd.
 A22 Yu An Rd, B Area,
 Tianzhu Airport Industrial Zone,
 Shunyi District,
 Beijing 101300
 Tel +86 10 80 49 80 00
 Fax +86 10 80 49 80 05

GERMANY
 Dräger Safety AG & Co. KGaA
 Revalstrasse 1
 23560 Lübeck
 Tel +49 451 882-2794
 Fax +49 451 882-4991

UNITED KINGDOM
 Draeger Safety UK Ltd.
 Blyth Riverside Business Park
 Blyth, Northumberland NE24 4RG
 Tel +44 1670 352 891
 Fax +44 1670 544 475

REGION EUROPE SOUTH
 Dräger Safety France SAS
 25, rue Georges Besse
 92182 Antony Cedex, France
 Tel +33 1 46 11 56 00
 Fax +33 1 40 96 97 20
Europe.South@draeger.com

USA
 Draeger Safety, Inc.
 505 Julie Rivers, Suite 150
 Sugar Land, TX 77478
 Tel +1 281 498 1082
 Fax +1 281 498 5190
info.gds@draeger.com

REGION ASIA PACIFIC
 Draeger Safety Asia Pte Ltd
 25 International Business Park
 #04-20/21 German Centre
 Singapore 609916
 Tel +65 6308 9400
 Fax +65 6308 9401
asia.pacific@draeger.com

**REGION CENTRAL
AND SOUTH AMERICA**
 Dräger Panama Comercial
 S. de R.L.
 Complejo Business Park,
 V tower, 10th floor
 Panama City
 Tel +507 377-9100
 Fax +507 377-9130
contactcsa@draeger.com

REGION MIDDLE EAST, AFRICA
 Dräger Safety AG & Co. KGaA
 Branch Office
 P.O. Box 505108
 Dubai, United Arab Emirates
 Tel +971 4 4294 600
 Fax +971 4 4294 699
contactuae@draeger.com